



- NOTES:
- 1) THE PRODUCT SHOWN HEREIN IS DESIGNED AND MANUFACTURED TO COMPLY WITH THE 2007 FLORIDA BUILDING CODE, 2009 SUPPLEMENTS.
  - 2) SHIM AS REQUIRED AT EACH INSTALLATION ANCHOR WITH LOAD BEARING SHIM. MAXIMUM ALLOWABLE SHIM STACK TO BE 1/4", SHIM WHERE SPACE OF 1/16" OR GREATER OCCURS.
  - 3) MATERIAL: ALUMINUM ALLOY 6063-T5.
  - 4) RESPONSIBILITY FOR SELECTION OF WINDOW PRODUCTS TO MEET ANY APPLICABLE LOCAL LAWS, BUILDING CODES, ORDINANCES OR OTHER SAFETY REQUIREMENTS REST SOLELY WITH THE ARCHITECT, BUILDING OWNER OR CONTRACTOR.
  - 5) POSTS BY OTHERS - THE POSTS SUPPLIED BY OTHERS SHALL:
    - A) PROVIDE STRUCTURAL STRENGTH TO CARRY IMPOSED LOADS.
    - B) FIRMLY ANCHOR ALL FASTENERS TO CARRY STRUCTURAL LOADS.
  - 6) USE FASTENER SCHEDULE ON ELEVATION VIEW.
  - 7) USE LATEX CAULK OR EQUIVALENT FOR PERIMETER SEAL AROUND BEHIND DOOR FLANGE
  - 8) ALL INSTALLATION ANCHORS MUST BE MADE OF CORROSION RESISTANT MATERIAL OR COATING
  - 9) SECTION 1622.1 SCREEN ENCLOSURES FOR HVHZ OF THE 2009 SUPPLEMENTS ALLOW THE USE OF VINYL AND ACRYLIC.

**OPTIONAL ACRYLIC GLAZING NOTE:**  
 WINDOW VENTS SHALL BE REMOVED WHEN WINDS EXCEED 75 MPH AS PER SECTION 2002.3 OF THE FLORIDA BUILDING CODE. REMOVABLE PANELS SHALL BE IDENTIFIED AS REMOVABLE BY A DECAL. THE IDENTIFICATION DECAL SHALL ESSENTIALLY STATE: "Removable panel shall be removed when wind speeds exceed 75 mph (34m/s)." DECALS SHALL BE PLACED SUCH THAT THE DECAL IS VISIBLE WHEN THE PANEL IS INSTALLED.

WINDOW CRAFTSMEN, INC.  
 6031 CLARK CENTER AVE.  
 SARASOTA, FLORIDA 34238

TITLE: ALUMINUM STORM DOOR INSTALLATION DETAILS		
ENGINEER: MARK A. SMITH	DRAWN BY: MAS	DATE: 9/5/08
DISCIPLINE: CIVIL	SCALE: N.T.S.	DWG. NO. WCI-SD-001
FL. REG. NO.: 55511	REV. LETTER: 0	SHEET 1