



OPTIONAL ACRYLIC GLAZING NOTE:
 WINDOW VENTS SHALL BE REMOVED WHEN WINDS EXCEED 75 MPH AS PER SECTION 2002.3 OF THE FLORIDA BUILDING CODE. REMOVABLE PANELS SHALL BE IDENTIFIED AS REMOVABLE BY A DECAL. THE IDENTIFICATION DECAL SHALL ESSENTIALLY STATE: "Removable panel shall be removed when wind speeds exceed 75 mph (34m/s)." DECALS SHALL BE PLACED SUCH THAT THE DECALS IS VISIBLE WHEN THE PANEL IS INSTALLED.

- NOTES:**
- 1) THE PRODUCT SHOWN HEREIN IS DESIGNED AND MANUFACTURED TO COMPLY WITH THE FLORIDA BUILDING CODE 8TH EDITION (2023).
 - 2) SHIM AS REQUIRED AT EACH INSTALLATION ANCHOR WITH LOAD BEARING SHIM. MAXIMUM ALLOWABLE SHIM STACK TO BE 1/4", SHIM WHERE SPACE OF 1/16" OR GREATER OCCURS.
 - 3) MATERIAL: ALUMINUM ALLOY 6063-T5.
 - 4) RESPONSIBILITY FOR SELECTION OF WINDOW PRODUCTS TO MEET ANY APPLICABLE LOCAL LAWS, BUILDING CODES, ORDINANCES OR OTHER SAFETY REQUIREMENTS REST SOLELY WITH THE ARCHITECT, BUILDING OWNER OR CONTRACTOR.
 - 5) POSTS BY OTHERS - THE POSTS SUPPLIED BY OTHERS SHALL:
 - A) PROVIDE STRUCTURAL STRENGTH TO CARRY IMPROSED LOADS.
 - B) FIRMLY ANCHOR ALL FASTENERS TO CARRY STRUCTURAL LOADS.
 - 6) USE FASTENER SCHEDULE ON ELEVATION VIEW.
 - 7) USE LATEX CAULK OR EQUIVALENT FOR PERIMETER SEAL AROUND BEHIND DOOR FLANGE
 - 8) ALL INSTALLATION ANCHORS MUST BE MADE OF CORROSION RESISTANT MATERIAL OR COATING
 - 9) SECTION 1622.1 SCREEN ENCLOSURES FOR HVHZ OF THE 2010 ALLOW THE USE OF VINYL AND ACRYLIC.

<p>TITLE: WINDOW CRAFTSMEN, INC. 6031 CLARK CENTER AVE. SARASOTA, FLORIDA 34238</p>			
<p>ENGINEER: MARK A. SMITH DISCIPLINE: CIVIL FL. REG. NO.: 55511</p>			
<p>DATE: 9/5/08</p>		<p>DWG. NO. SD-001</p>	
<p>SCALE: N.T.S.</p>		<p>REV. LETTER: D</p>	
<p>PREPARED BY: MARK SMITH, P.E. 3738 KINGSWOOD DRIVE, SARASOTA, FL 34232 PH. 941-993-9620</p>		<p>SHEET 1</p>	